

SPECIFICATION



DucoClose G 35 Z

Make :

Duco ‘Ventilation & Sun Control’

Type :

DucoClose G 35Z,
closable aluminium recess-mounting wall vent

Description :

DucoClose G 35Z is a closable aluminium “recess-mounting” wall vent that provides intensive ventilation. The aerofoils are beautifully finished outside (Z shape) and inside (rounded). The moveable Z aerofoils allow for adjustable ventilation with a choice of manual or electric operation. The vents come in a standard F1 version (15-20 µm), although all RAL colours are available (60-80 µm). DucoClose is also available with an (optional) insect and vermin mesh.

Material :

a) Aluminium : ISO 209-89: 6063

Surface treatment :

Standard natural anodised finish (15-20 µm)
(VB6/A20/VOM1)

Special bronze anodised finish

Stove enamelled and polyester powder coated (60-80µm)

b) Synthetic parts : Glass fibre reinforced polyamide PA 6.6
(vent valves)

Dimensions :

Ordering dimensions : Width (-10 mm clearance) x Height (-10 mm clearance) of the wall aperture

Minimum height : 273 mm, then in steps of 50 mm

Custom dimensions available.

Control options :

Manual or electrical

Colour fastness :

Anodised, no discolouration ; stove enamelled colour fast

Fastenings : Screws and plugs supplied as standard

Type of aerofoil blade : 35 Z

Height of aerofoil blades (mm) : 40

Blade pitch (mm) : 50

Frame depth (mm) : 42

SPECIFICATION



Minimum height (mm) :

- manual operation : 223.5 mm
- electrical operation : 473.5 mm

Free surface area :

Open position : 51 %

Net airflow at 1 Pa to NEN 1087 :

Open position : 39 %